

### Refrigerator Water Filter Models:

**SW-A1, SW-G1, SW-G2, SW-G3, SW-G6, SW-G7, SW-H1, SW-L1,  
SW-L2, SW-M1, SW-M2, SW-S1, SW-S2, SW-W1, SW-W2, SW-W3, SW-W4**

This system has been tested according to NSF/ANSI Standard 42, 53, 372, 401, P473 and CSA B483.1 for reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standards 42, 53, 372, 401, P473 and CSA B483.1.

Contaminant	% of reduction	Influent Concentration	Max Allowable	Contaminant	% of reduction	Influent Concentration	Max Allowable
CHLORINE	>97%	2.0 mg/L	1.0 mg/L	HALOKETONES (HK):**			
ALACHLOR†	>98%	0.050	0.001	1,1-DICHLORO-2-PROPANONE†	99%	0.0072	0.0001
Asbestos	99.98%	189 MFL	99%	1,1,1-TRICHLORO-2-PROPANONE‡	96%	0.0082	0.0003
ATRAZINE**	>97%	0.100	0.003	HEPTACHLOR**	>99%	0.25	0.00001
BENZENE**	>99%	0.081	0.001	HEPTACHLOR EPOXIDE**	98%	0.0107	0.0002
BISPHENOL‡	99.1%	2.058 mg/L	<0.300mg/L	HEXACHLOROBUTADIENE (Perchlorobutadiene)**	>98%	0.044	0.001
BROMODICHLOROMETHANE (TTHM)**	>99.8%	0.300	0.015	HEXACHLOROCYCLOPENTADIENE**	>99%	0.060	0.000002
BROMOFORM (TTHM)**	>99.8%	0.300	0.015	IBUPROFEN†	96.7%	0.432 mg/L	<0.060 mg/L
CARBOFURAN (Furadan)**	>99%	0.19	0.001	LINDANE**	>99%	0.055	0.00001
Carbon Tetrachloride	>95%	0.014	0.005	METHOXYCHLOR**	>99%	0.050	0.0001
CHLOROBENZENE (Monochlorobenzene)**	>99%	0.077	0.001	Methylbenzene (see TOLUENE)**	>99%	0.078	0.001
CHLOROPICRIN**	99%	0.015	0.0002	Mercury (pH 6.5)†	74.9%	0.0059	0.002
CHLOROFORM (TTHM)* (surrogate chemical)†	>99.8%	0.300	0.015	Mercury (pH 8.5)†	97.8%	0.0061	0.002
2, 4-D*	†98%	0.110	0.0017	Monochlorobenzene (see CHLOROBENZENE)**	>99%	0.077	0.001
CYST (Giardi; Cryptosporidium; Entamoeba; Toxoplasma)†	>99.95%	MINIMUM 50,000/L	<sup>99.95% REDUCTION REQUIREMENT</sup>	NAPROXEN†	95.3%	0.130 mg/L	<0.020 mg/L
Cryptosporidium (see CYST)†	>99.95%	MINIMUM 50,000/L	<sup>99.95% REDUCTION REQUIREMENT</sup>	NONYLPHENOL†	97.1%	2.058 mg/L	<0.200 mg/L
DBCP (see Dibromochloropropane)**	>99%	0.052	0.00002	PCE (see Tetrachloroethylene)†	>96%	0.014	0.005
1,2-DCA (see 1,2-DICHLOROETHANE)**	95%	0.088	0.0048	PENTACHLOROPHENOL**	>99%	0.096	0.001
1,1,-DCE (see 1,1-DICHLOROETHYLENE)**	>99%	0.083	0.001	Perchlorobutadiene (see HEXACHLOROBUTADIENE)**	>98%	0.044	0.001
DIBROMOCHLOROMETHANE (THM; Chlorobromomethane)**	>99.8%	0.300	0.015	PFOA†	98.0%	0.0005 mg/L	<0.00007 mg/L
DIBROMOCHLOROPROPANE (DBCP)**	>99%	0.052	0.00002	PFOS†	98.0%	0.001 mg/L	<0.00007 mg/L
o-DICHLOROBENZENE (1,2 Dichlorobenzene)**	>99%	0.080	0.001	Phenitoin†	94.7%	0.2173 mg/L	<.030 mg/L
p-DICHLOROBENZENE (para-Dichlorobenzene)	>98%	0.040	0.001	Propylene Dichloride (see 1,2-DICHLOROPROPANE)**	>99%	0.080	0.001
1,2-DICHLOROETHANE (1,2-DCA)**	95%	0.088	0.0048	SIMAZINE**	>97%	0.120	0.004
1,1-DICHLOROETHYLENE (1,1-DCE)**	>99%	0.083	0.001	STYRENE (Vinylbenzene)**	>99%	0.150	0.0005
CIS-1,2-DICHLOROETHYLENE**	>99%	0.170	0.0005	1,1,1,-TCA (see 1,1,1 - TRICHLOROETHANE)**	95%	0.084	0.0046
TRANS-1,2- DICHLOROETHYLENE**	>99%	0.086	0.001	1,2,4-Trichlorobenze	>99%	0.215	0.07
1,2-DICHLOROPROPANE (Propylene Dichloride)**	>99%	0.080	0.001	TCE (see TRICHLOROETHYLENE)**	>99%	0.180	0.0010
CIS-1,3- DICHLOROPROPYLENE**	>99%	0.079	0.001	1,1,2,2- TETRACHLOROETHANE**	>99%	0.081	0.001
DINOSEB†	99%	0.170	0.0002	TETRACHLOROETHYLENE*	>99%	0.081	0.001
EDB (see ETHYLENE DIBROMIDE)**	>99%	0.044	0.00002	TOLUENE (Methylbenzene)**	>99%	0.078	0.001
ENDRIN	99%	0.053	0.00059	TOXAPHENE	>92.9%	0.015 +/- 10%	0.003
Entamoeba (see CYSTS)†	99.95%	MINIMUM 50,000/L	<sup>99.95% REDUCTION REQUIREMENT</sup>	2,4,5-TP (Silvex)**	99%	0.270	0.0016
ESTRONE†	96.9%	0.1388 mg/L	<0.020 mg/L	Toxoplasma (see CYST)†	>99.95%	MINIMUM 50,000/L	<sup>99.95% REDUCTION REQUIREMENT</sup>
ETHYLBENZENE**	>99%	0.088	0.001	TRIBROMOACETIC ACID**		0.042	0.001
ETHYLENE DIBROMIDE (EDB)**	>99%	0.044	0.00002	1,1,1-TRICHLOROETHANE (1,1,1-TCA)**	95%	0.084	0.0046
Furadan (see CARBOFURAN)**	>99%	0.19	0.001	1,1,2-TRICHLOROETHANE**	>99%	0.150	0.0005
Giardia Lamblia (see CYST)†	>99.95%	MINIMUM 50,000/L	<sup>99.95% REDUCTION REQUIREMENT</sup>	TRICHLOROETHYLENE (TCE)**	>99%	0.180	0.0010
HALOACETONITRILES (HAN)**				TRIAIOMETHANES (TTHM) (Chloroform; Bromoform; Bromodichloromethane; Dibromochloromethane)†	>99.8%	0.300	0.015
BROMOCHLOROACETONITRILE†	98%	0.022	0.0005	Unsym-Trichlorobenzene (see 1,2,4-TRICHLOROBENZENE)**	>99%	0.160	0.0005
DIBROMOACETONITRILE†	98%	0.024	0.0006	Vinylbenzene (see STYRENE)**	>99%	0.150	0.0005
HALOACETONITRILES (HAN)**				XYLENES (TOTAL)**	>99%	0.070	0.001
DICHLOROACETONITRILE†	98%	0.0096	0.0002				
TRICHLOROACETONITRILE†	98%	0.015	0.0003				

† Not tested or certified by NSF International.

### Filter Specifications

Flow Rate:	0.5 gpm / 1.89 lpm
Operating Temperature:	33 - 100°F (0.6°C - 38°C)
Operating Pressure:	30 psi (207 kPa) - 100 psi (689 kPa)
Capacity:	300 gallons (1,136 L) or six months



Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of chlorine taste and odor, Endrin, Trichlorobenze, and p-Dichlorobenzene. Refer to Performance Data Sheet for a complete list of claims.



Certified by IAPMO R&T against NSF/ANSI Standard 42, 53, 372, 401, P473 and CSA B483.1 for the reduction of Chlorine taste and odor, Cyst, Mercury, Asbestos, Pharmaceuticals (such as Naproxen, Ibuprofen and Phenitoin), BPA, and PFOA/PFOS. Refer to Performance Data Sheet for a complete list of claims.

The compounds under NSF/ANSI 401 have been deemed as 'incidental contaminants / emerging compounds'.

**Limited Warranty:** This filter hereunder shall be free from material defects in material and workmanship for a period of one (1) year from the date of purchase. To reduce the risk of property damage due to water leakage, this filter MUST be installed in accordance with the manufacturer's specifications and installations. This filter unit must be replaced every 6 months, at the rated capacity, or sooner if reduced water flow occurs. Protect form freezing. Failure to follow instructions and operating specifications will void your warranty. Further, manufacturer assumes no responsibility or liability for damages arising out of misuse of the product.

Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts. The system conforms to NSF/ANSI 42, 53, 372, 401, P473 and CSA B483.1 for the specific performance claims as verified and substantiated by test data. See above for individual contaminants and reduction performance. Note: Testing was performed under standard laboratory conditions, actual performance may vary.

System to be used with municipal or well water sources treated and tested on regular basis to ensure bacteriological safe quality. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. Manufactured by Aquamor, LLC, Temecula, CA.